

www.geoluxe.com | info@geoluxe.com f 9 y 0 t









PRECAUTIONS

1. Chemicals to AVOID

surface: use following cleaning agents to clean the it long lasting, it is recommended NOT to To maintain its sheen of all finishes and keep

ammonia, caustic soda, sodium hypochlorite Glass etching acid or hydrofluoric acid (HF) Alkaline solution with pH higher than 10 e.g.

2. Tools to AVOID

- Abrasive cleaner

well: light, it is recommended **NOT** to use following degree of glossiness and the reflection of of scratch such as light & dark color, the surface as the same way they do on others as tools which possibly affect GEOLUXE®'s there remain other factors affecting visibility giving its hardness and unmatched durability, Despite processing with high temperature

- Ceramic knives
- Metal scouring pads
- Sharp tools
- china plate, porcelain) Objects as hard as GEOLUXE® (e.g. bone

3. Things to remember

GEOLUXE® surface as soon as possible. 3.1 To prevent staining, it is recommended to remove any kind of liquid remained on

test the effect on a small area. DO NOT leave recommended period of time. If other agents 3.2 Please STRICTLY FOLLOW the instruction them on GEOLUXE®'s surface longer than 10 are used, please dilute them with water and using the specified cleaning agents and a

their instruction. each local area. For your safety, it is recommended to read their cautions and follow 3.3 Due to the different cleaning agents in

4. Things to be aware

- requires special attention. DO NOT hit it with 4.1 Please be noted that the edge area is the probably causes chipping. pointed object or heavy impact since it most sensitive part of a countertop, which
- leave the water dried on the surface. 4.2 To avoid hard water stain, please do not

or Hard Water Stain

Rust

Lime and Rust Stain

Remover)

(e.g. Zep: Calcium, Acid Detergent Limescale

Soap

4.3 For outdoor use, please cover your 4.4 After following the guideline for difficult may be used for better stain removal. stain removal, for honed surface, soft brush countertop when not in use to avoid dirt.

Residue & Grout Cement-based

Grease

GUIDELINE FOR DIFFICULT STAIN REMOVAL

STAIN	CLEANING AGENT
Coffee	
Wine	
Soft Drink	Multi-purpose Cleaner
Fruit Juice	Multi-purpose Cleaner)

Advanced step

Cooking Oil

(Only if the stain persists)



Soaking Tool: cotton pad Time: 10 minutes



Tool: a soft damp cloth



Rinsing and drying Tool: a soft damp cloth

evaporation of cleaning agent. cover the cotton pad with clear tape to prevent To make soaking method more effective, please 〒

CAUTION

DO NOT use high alkaline solution for soaking agent as recommended method. Instead, please strictly use the cleaning

Note: Repeat the process with longer soaking time, if necessary

	(e.g. Stonetech: Epoxy	& Coating Stripper	Epoxy Grout Haze	
(<			ار

Candle Wax

Soaking
Tool: a soft dry cloth
Time: 1 minute

& Coating Stripper)

Grout Haze

different depending on types of stains as shown in the table.

Paraffin

Epoxy

Three main cleaning methods are used to clean the surface. Their cleaning sequence is

SPECIAL CLEANING METHODS

soap and warm water. After cleaning, rinse with clean water and completely dry with microfiber For general cleaning, simply use a soft damp cloth to wipe your GEOLUXE® surface with mild GENERAL CLEANING METHOD



Rubbing
Tool: a soft dry cloth





Rinsing and drying Tool: a soft damp doth

CAUTION

on the surface more than 5 minutes when Epoxy grout haze & coating stripper is left Stain resistance of GEOLUXE® might be reduced

Note: Repeat the process, if necessary

Tool: a soft dry cloth



Note: Repeat the process, if necessary



the surface, and can be easily removed Metal mark may resemble scratch but it is actually a residue from metal rubbing against



Rinsing and drying

the stain for a specific period of time.

If the stain persists, saturate the sheet of cotton pad or tool

Metal Mark

Metal Polish Cream/Liquid (e.g. Brasso: Metal Polish,

Wenol: Metal Polish)

the stain is completely gone.

Rub the surface with recommended cleaning agent and tools until

specified with recommended cleaning agent, and then place it on

with clean water and completely dry with microfiber cloth. Wipe out the leftover cleaning agent with recommended tools, rinse

If the stain still remains after all procedures have been done, please contact GEOLUXE® via info@geoluxe.com